TEST REPORT

Applicant's Name	:	FOSHAN KAICHENG LIGHTING CO., LTD
Address	:	No.16 Xingye West Road, Shishan Town, Nanhai District, Foshan, 528000 Guangdong, P.R. China
Product Name	:	LED floodlight
Trade Mark	:	N/A
Model(s)	:	EK05-EC 100W
Testing Laboratory	:	Shenzhen DACE Testing Technology Co., Ltd.
Address	:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Test Date	:	Jun. 23, 2025 - Nov. 24, 2025
Date of Report	:	Nov. 29, 2025
Report No.	:	DACE251119025RL001

Note:This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample

Revision History Of Report

Version	Description	REPORT No.	Modified information
A0	Original	DACE251119025RL001	None

TEST REPORT

000009843

Reference No.:	DACE251119025RL001
Compiled by (name + signature):	Parker Chen
Approved by (name + signature):	Calvin Chen
Date of issue:	Nov. 29, 2025

Testing laboratory

Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Testing location:	Same as above

Client

Name:	FOSHAN KAICHENG LIGHTING CO., LTD
Address:	No.16 Xingye West Road, Shishan Town, Nanhai District, Foshan, 528000 Guangdong, P.R. China

Test specification

Standard:	EU 2019/2020 EU 2019/2015 EU 2021/340
Test procedure:	COMMISSION REGULATION (EU) 2019/2020 of 1 October 2019 laying down ecodesign requirements for light sources and separate control gears pursuant to Directive 2009/125/EC of the European Parliament and of the Council and repealing Commission Regulations (EC) No 244/2009, (EC) No 245/2009 and (EU) No 1194/2012
Test Report Form No.:	EU2019A
Master TRF:	2022-10

Test item

Product Name:	LED floodlight
Trade Mark:	N/A
Model(s):	EK05-EC 100W
Manufacturer's name:	FOSHAN KAICHENG LIGHTING CO., LTD
Address:	No.16 Xingye West Road, Shishan Town, Nanhai District, Foshan, 528000 Guangdong, P.R. China

TEST Standard	
Measured parameter	**Reference**
Lumen	IEC62717:2014+A1:2015+A2:2019
Lamp efficacy, luminous efficacy	IEC62717:2014+A1:2015+A2:2019.
Lamp survival factor	IEC62717:2014+A1:2015+A2:2019
Lumen maintenance	IEC62717:2014+A1:2015+A2:2019
Chromaticity coordinates	EN13032-4:2015
Colour consistency	IEC62717:2014+A1:2015+A2:2019
CCT	EN13032-4:2015
CRI	EN13032-4:2015
Lamp dimensions	IEC62717:2014+A1:2015+A2:2019
Dimmability	IEC62717:2014+A1:2015+A2:2019
Beam angle	IEC62717:2014+A1:2015+A2:2019, IEC/TR 61341-2010
Peak intensity	IEC62717:2014+A1:2015+A2:2019, IEC/TR 61341-2010
Cone lumen	L2(AP)005

Test item particulars:	
Model name..... :	EK05-EC 100W
Lighting type..... :	☒ directional ☐ non-directional
Rated voltage and frequency..... :	220-240VAC 50/60Hz
Rated wattage..... :	100W
Lamp cap..... :	N/A
Nominal luminous flux Φ..... :	6500K: 8070lm 4500K: 8870lm 3000K: 8020lm
Useful luminous flux (Φuse) ..... :	6500K: 7069lm 4500K: 7770lm 3000K: 7026lm
Declared ηTM (lm/W)..... :	6500K: 97lm/W 4500K: 104lm/W 3000K: 97lm/W
Declared Colour rendering (CRI)..... :	80
Declared Displacement factor for LED and OLED MLS(DF)..... :	0.90
Declared Lumen maintenance factor for LED and OLE..... :	96.00%
Declared Survival factor for LED and OLED. :	90.00%
Declared colour consistency for LED and OLED ..... :	6
Declared beam angle for DLS..... :	110
Declared lamp life..... :	36000h
Declared color temperature ..... :	6500K/4500K/3000K
Declared Flicker for LED and OLED MLS..... :	1.0
Declared Stroboscopic effect for LED and OLED MLS..... :	0.4
Test case verdicts	
Test case does not apply to the test object... :	N/A
Test item does meet the requirement..... :	P(ass)
Test item does not meet the requirement..... :	F(ail)
Testing	
Date of receipt of test item ..... :	Jun. 23, 2025
Date(s) of performance of test..... :	Jun. 23, 2025 - Nov. 24, 2025

General remarks:

This test report shall not be reproduced except in full without the written approval of the testing laboratory.

The test results presented in this report relate only to the item tested.

"(see remark #)" refers to a remark appended to the report.

"(see appended table)" refers to a table appended to the report.

Appendix I: Test results--Tabel 1: Initial test results: (6500K)

		Test Result				P
Sample No.	Measured voltage(V)	Measured current (mA)	Measured power(W)	Initial Φuse (lm)	Beam angle (°) for DLS	--
1#	AC230	455	98.08	8068	110	--
2#	AC230	455	98.08	8017	109	--
3#	AC230	454	97.86	8155	110	--
4#	AC230	454	97.86	8011	110	--
5#	AC230	455	98.08	8019	110	--
6#	AC230	455	98.08	8139	109	--
7#	AC230	454	97.86	8061	111	--
8#	AC230	455	98.08	8146	110	--
9#	AC230	455	98.08	8134	110	--
10#	AC230	454	97.86	8020	109	--
Average	**AC230**	**455**	**97.99**	**8077**	**110**	**--**
Sample No.	Colour rendering (CRI)	Displacement factor(DF)	Colour consistency	Flicker(Pst LM)	Stroboscopic effect(SVM)	--
1#	82	0.90	5.9	1.0	0.4	--
2#	81	0.90	6.0	1.0	0.4	--
3#	82	0.90	6.0	1.0	0.4	--
4#	82	0.90	6.0	1.0	0.4	--
5#	81	0.90	5.9	1.0	0.4	--
6#	82	0.90	5.9	1.0	0.4	--
7#	82	0.90	6.0	1.0	0.4	--
8#	82	0.90	6.0	1.0	0.4	--
9#	81	0.90	5.9	1.0	0.4	--
10#	82	0.90	6.0	1.0	0.4	--
Average	**82**	**0.90**	**6.0**	**1.0**	**0.4**	**--**
Required	**CRI≥80**	**DF≥XX**	**SDCM≤6**	**Pst LM≤1,0**	**SVM≤0,4**	--

Tabel 2: Initial test results: (6500K)

		Test Result					P
Sample No.	Initial Φuse (lm)	Efficacy factor (F)	CRI factor (R)	Threshold efficacy (η)	End loss factor (L)	Correction factor (C)	Ponmax
1#	8068	0.85	1.01	120	1.5	1.23	100.13
2#	8017	0.85	1.01	120	1.5	1.23	99.51
3#	8155	0.85	1.01	120	1.5	1.23	101.19
4#	8011	0.85	1.01	120	1.5	1.23	99.43
5#	8019	0.85	1.01	120	1.5	1.23	99.53
6#	8139	0.85	1.01	120	1.5	1.23	100.99
7#	8061	0.85	1.01	120	1.5	1.23	100.04
8#	8146	0.85	1.01	120	1.5	1.23	101.08
9#	8134	0.85	1.01	120	1.5	1.23	100.93
10#	8020	0.85	1.01	120	1.5	1.23	99.54
Average	**8077**	**0.85**	**1.01**	**120**	**1.5**	**1.23**	**100.24**
Factor	N/A	☐ 1.00 for NDLS ☒ 0.85 for DLS	☐ 0.65 for CRI≤25, ☒ (CRI+80)/160 for CRI>25	120.0 for LED	1.5 for LED	☐ NDLS & NMLS: 1.00 ☐ NDLS & MLS: 1.08 ☐ DLS & NMLS: 1.15 ☒ DLS & MLS: 1.23	Pon= Cx(L+ Φuse/(Fx η)xR

Tabel 3: Initial test results for Energy efficiency classes: (6500K)

		Test Result				P
Sample No.	Initial Φuse (lm)	Initial Pon(W)	F_{TM}	ηTM (lm/W)	Test Energy efficiency class	Declare Energy efficiency class
1#	8068	98.08	1.176	97	F	F
2#	8017	98.08	1.176	96	F	F
3#	8155	97.86	1.176	98	F	F
4#	8011	97.86	1.176	96	F	F
5#	8019	98.08	1.176	96	F	F
6#	8139	98.08	1.176	98	F	F
7#	8061	97.86	1.176	97	F	F
8#	8146	98.08	1.176	98	F	F
9#	8134	98.08	1.176	98	F	F
10#	8020	97.86	1.176	96	F	F
Average	**8077**	97.99	**1.176**	**97**	**F**	**F**

Energy efficiency class:

A: 210 ≤ ηTM
B: 185 ≤ ηTM < 210
C: 160 ≤ ηTM < 185
D: 135 ≤ ηTM < 160
E: 110 ≤ ηTM < 135
F: 85 ≤ ηTM < 110
G: ηTM < 85

☐ NDLS & MLS: 1.00
☐ NDLS & NMLS: 0.926
☒ DLS & MLS: 1.176
☐ DLS & NMLS: 1.089

ηTM = (Φuse/Pon) × FTM (lm/W).

Appendix I: Test results--Tabel 1: Initial test results: (4500K)

		Test Result				P
Sample No.	Measured voltage(V)	Measured current (mA)	Measured power(W)	Initial Φuse (lm)	Beam angle (°) for DLS	--
1#	AC230	463	100.10	8867	110	--
2#	AC230	463	100.10	8816	109	--
3#	AC230	462	99.88	8954	110	--
4#	AC230	462	99.88	8810	110	--
5#	AC230	463	100.10	8818	110	--
6#	AC230	463	100.10	8938	109	--
7#	AC230	462	99.88	8860	111	--
8#	AC230	463	100.10	8945	110	--
9#	AC230	463	100.10	8933	110	--
10#	AC230	462	99.88	8819	109	--
Average	**AC230**	**463**	**100.01**	**8876**	**110**	**--**
Sample No.	Colour rendering (CRI)	Displacement factor(DF)	Colour consistency	Flicker(Pst LM)	Stroboscopic effect(SVM)	--
1#	84	0.90	5.9	1.0	0.4	--
2#	85	0.90	6.0	1.0	0.4	--
3#	85	0.90	6.0	1.0	0.4	--
4#	84	0.90	6.0	1.0	0.4	--
5#	85	0.90	5.9	1.0	0.4	--
6#	84	0.90	5.9	1.0	0.4	--
7#	86	0.90	6.0	1.0	0.4	--
8#	84	0.90	6.0	1.0	0.4	--
9#	85	0.90	5.9	1.0	0.4	--
10#	84	0.90	6.0	1.0	0.4	--
Average	**85**	**0.90**	**6.0**	**1.0**	**0.4**	**--**
Required	**CRI≥80**	**DF≥XX**	**SDCM≤6**	**Pst LM≤1,0**	**SVM≤0,4**	--

Tabel 2: Initial test results: (4500K)

		Test Result					P
Sample No.	Initial Φuse (lm)	Efficacy factor (F)	CRI factor (R)	Threshold efficacy (η)	End loss factor (L)	Correction factor (C)	Ponmax
1#	8867	0.85	1.03	120	1.5	1.23	112.03
2#	8816	0.85	1.03	120	1.5	1.23	111.40
3#	8954	0.85	1.03	120	1.5	1.23	113.11
4#	8810	0.85	1.03	120	1.5	1.23	111.33
5#	8818	0.85	1.03	120	1.5	1.23	111.43
6#	8938	0.85	1.03	120	1.5	1.23	112.92
7#	8860	0.85	1.04	120	1.5	1.23	113.03
8#	8945	0.85	1.03	120	1.5	1.23	113.00
9#	8933	0.85	1.03	120	1.5	1.23	112.85
10#	8819	0.85	1.03	120	1.5	1.23	111.44
Average	**8876**	**0.85**	**1.03**	**120**	**1.5**	**1.23**	**112.25**
Factor	N/A	☐ 1.00 for NDLS ☒ 0.85 for DLS	☐ 0.65 for CRI≤25, ☒ (CRI+80)/160 for CRI>25	120.0 for LED	1.5 for LED	☐ NDLS & NMLS: 1.00 ☐ NDLS & MLS: 1.08 ☐ DLS & NMLS: 1.15 ☒ DLS & MLS: 1.23	Pon= Cx(L+ Φuse/(Fx η)xR

Tabel 3: Initial test results for Energy efficiency classes: (4500K)

		Test Result				P
Sample No.	Initial Φuse (lm)	Initial Pon(W)	F_{TM}	ηTM (lm/W)	Test Energy efficiency class	Declare Energy efficiency class
1#	8867	100.10	1.176	104	F	F
2#	8816	100.10	1.176	104	F	F
3#	8954	99.88	1.176	105	F	F
4#	8810	99.88	1.176	104	F	F
5#	8818	100.10	1.176	104	F	F
6#	8938	100.10	1.176	105	F	F
7#	8860	99.88	1.176	104	F	F
8#	8945	100.10	1.176	105	F	F
9#	8933	100.10	1.176	105	F	F
10#	8819	99.88	1.176	104	F	F
Average	**8876**	100.01	**1.176**	**104**	**F**	**F**

Energy efficiency class:

A: 210 ≤ ηTM
B: 185 ≤ ηTM < 210
C: 160 ≤ ηTM < 185
D: 135 ≤ ηTM < 160
E: 110 ≤ ηTM < 135
F: 85 ≤ ηTM < 110
G: ηTM < 85

☐ NDLS & MLS: 1.00
☐ NDLS & NMLS: 0.926
☒ DLS & MLS: 1.176
☐ DLS & NMLS: 1.089

ηTM = (Φuse/Pon) × FTM (lm/W).

Appendix I: Test results--Tabel 1: Initial test results: (3000K)

		Test Result				P
Sample No.	Measured voltage(V)	Measured current (mA)	Measured power(W)	Initial Φuse (lm)	Beam angle (°) for DLS	--
1#	AC230	454	97.85	8016	110	--
2#	AC230	454	97.85	7965	109	--
3#	AC230	453	97.64	8103	110	--
4#	AC230	453	97.64	7959	110	--
5#	AC230	454	97.85	7967	110	--
6#	AC230	454	97.85	8087	109	--
7#	AC230	453	97.64	8009	111	--
8#	AC230	454	97.85	8094	110	--
9#	AC230	454	97.85	8082	110	--
10#	AC230	453	97.64	7968	109	--
Average	**AC230**	**454**	**97.77**	**8025**	**110**	**--**
Sample No.	Colour rendering (CRI)	Displacement factor(DF)	Colour consistency	Flicker(Pst LM)	Stroboscopic effect(SVM)	--
1#	82	0.90	5.9	1.0	0.4	--
2#	81	0.90	6.0	1.0	0.4	--
3#	82	0.90	6.0	1.0	0.4	--
4#	82	0.90	6.0	1.0	0.4	--
5#	81	0.90	5.9	1.0	0.4	--
6#	82	0.90	5.9	1.0	0.4	--
7#	82	0.90	6.0	1.0	0.4	--
8#	82	0.90	6.0	1.0	0.4	--
9#	81	0.90	5.9	1.0	0.4	--
10#	82	0.90	6.0	1.0	0.4	--
Average	**82**	**0.90**	**6.0**	**1.0**	**0.4**	**--**
Required	**CRI≥80**	**DF≥XX**	**SDCM≤6**	**Pst LM≤1,0**	**SVM≤0,4**	--

Tabel 2: Initial test results: (3000K)

		Test Result					P
Sample No.	Initial Φuse (lm)	Efficacy factor (F)	CRI factor (R)	Threshold efficacy (η)	End loss factor (L)	Correction factor (C)	Ponmax
1#	8016	0.85	1.01	120	1.5	1.23	99.49
2#	7965	0.85	1.01	120	1.5	1.23	98.87
3#	8103	0.85	1.01	120	1.5	1.23	100.55
4#	7959	0.85	1.01	120	1.5	1.23	98.80
5#	7967	0.85	1.01	120	1.5	1.23	98.90
6#	8087	0.85	1.01	120	1.5	1.23	100.36
7#	8009	0.85	1.01	120	1.5	1.23	99.41
8#	8094	0.85	1.01	120	1.5	1.23	100.44
9#	8082	0.85	1.01	120	1.5	1.23	100.30
10#	7968	0.85	1.01	120	1.5	1.23	98.91
Average	**8025**	**0.85**	**1.01**	**120**	**1.5**	**1.23**	**99.60**
Factor	N/A	☐ 1.00 for NDLS ☒ 0.85 for DLS	☐ 0.65 for CRI≤25, ☒ (CRI+80)/160 for CRI>25	120.0 for LED	1.5 for LED	☐ NDLS & NMLS: 1.00 ☐ NDLS & MLS: 1.08 ☐ DLS & NMLS: 1.15 ☒ DLS & MLS: 1.23	Pon= Cx(L+ Φuse/(Fx η)xR

Tabel 3: Initial test results for Energy efficiency classes: (3000K)

		Test Result				P
Sample No.	Initial Φuse (lm)	Initial Pon(W)	F_{TM}	ηTM (lm/W)	Test Energy efficiency class	Declare Energy efficiency class
1#	8016	97.85	1.176	96	F	F
2#	7965	97.85	1.176	96	F	F
3#	8103	97.64	1.176	98	F	F
4#	7959	97.64	1.176	96	F	F
5#	7967	97.85	1.176	96	F	F
6#	8087	97.85	1.176	97	F	F
7#	8009	97.64	1.176	96	F	F
8#	8094	97.85	1.176	97	F	F
9#	8082	97.85	1.176	97	F	F
10#	7968	97.64	1.176	96	F	F
Average	**8025**	97.77	**1.176**	**97**	**F**	**F**

Energy efficiency class:

A: 210 ≤ ηTM
B: 185 ≤ ηTM < 210
C: 160 ≤ ηTM < 185
D: 135 ≤ ηTM < 160
E: 110 ≤ ηTM < 135
F: 85 ≤ ηTM < 110
G: ηTM < 85

☐ NDLS & MLS: 1.00
☐ NDLS & NMLS: 0.926
☒ DLS & MLS: 1.176
☐ DLS & NMLS: 1.089

ηTM = (Φuse/Pon) × FTM (lm/W).

Table 4: Test results of survival factor and Lumen maintenance: (3000K)




	Test Result			P
Sample No.	Initial Φuse (lm)	3600H Φuse (lm)	XLMF,MIN% at 3600H	survival factor at 3600H
1#	8016	7785	97.12%	No damage
2#	7965	7735	97.11%	No damage
3#	8103	7872	97.15%	No damage
4#	7959	7729	97.11%	No damage
5#	7967	7736	97.10%	No damage
6#	8087	7856	97.14%	No damage
7#	8009	7779	97.13%	No damage
8#	8094	7863	97.15%	No damage
9#	8082	7851	97.14%	No damage
10#	7968	7738	97.11%	No damage
Average	**8025**	**7794**	**97.13%**	**100%**
Required	--	--	**96.00%**	**90%**

Table 5: Test results of No-load power(Pno), Standby power(Psb) and Networked standby power(Pnet) (3000K)

	Test Result			N/A
Sample No.	Pno (W)	Psb (W)	Pnet (W)	
1#	--	--	--	
2#	--	--	--	
3#	--	--	--	
4#	--	--	--	
5#	--	--	--	
6#	--	--	--	
7#	--	--	--	
8#	--	--	--	
9#	--	--	--	
10#	--	--	--	
Average	**--**	**--**	**--**	
Required	**<0.5W**	**<0.5W**	**<0.5W**	

Product information sheet

Supplier's name or trade mark: FOSHAN KAICHENG LIGHTING CO., LTD			
Supplier's address: No.16 Xingye West Road, Shishan Town, Nanhai District, Foshan, 528000 Guangdong, P.R. China			
Model identifier: EK05-EC 100W			
Type of light source:			
Lighting technology used:	☐ CFL ☒ LED ☐ HID ☐ Others:	Non-directional or directional:	☐ NDLS ☒ DLS
Light source cap-type (or other electric interface)	/		
Mains or non-mains:	☒ MLS ☐ NMLS	Connected light source (CLS):	☐ Yes ☒ No
Colour-tuneable light source:	☒ Yes ☐ No	Envelope:	☐ Yes ☒ No
High luminance light source:	☐ Yes ☒ No		
Anti-glare shield:	☐ Yes ☒ No	Dimmable:	☐ Yes ☐ Only with specific dimmers ☒ No
Product parameters			
Parameter	220-240VAC 50/60Hz 100W	Parameter	/
General product parameters:			
Energy consumption in on-mode (kWh/1 000h),rounded up to the nearest integer	98kWh/1000h(6500K) 100kWh/1000h(4500K) 98kWh/1000h(3000K)	Energy efficiency class	F

<table>
<tr><td colspan="2">Useful luminous flux (Φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)</td><td>8070 in a sphere (6500K)
8870 in a sphere (4500K)
8020 in a sphere (3000K)</td><td>Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set</td><td>6500K/4500K/3000K</td></tr>
<tr><td colspan="2">On-mode power (Pon), expressed in W</td><td>100.0</td><td>Standby power (Psb), expressed in W and rounded to the second decimal</td><td>/</td></tr>
<tr><td colspan="2">Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal</td><td>No Networked standby power</td><td>Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set</td><td>80</td></tr>
<tr><td rowspan="3">Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)</td><td>Height</td><td>180</td><td rowspan="3">Spectral power distribution in the range 250 nm to 800 nm, at full-load</td><td rowspan="3">6500K

4500K

3000K
</td></tr>
<tr><td>Width</td><td>255</td></tr>
<tr><td>Depth</td><td>28</td></tr>
<tr><td colspan="2">Claim of equivalent power</td><td>☐ Yes
☒ —</td><td>If yes, equivalent power (W)</td><td>/</td></tr>
</table>

		Chromaticity coordinates (x and y)	6500K x: 0.314 y: 0.340 4500K x: 0.368 y: 0.369 3000K x: 0.438 y: 0.406
Parameters for directional light sources:			
Peak luminous intensity (cd)	3338	Beam angle in degrees, or the range of beam angles that can be set	110
Parameters for LED and OLED light sources:			
R9 colour rendering index value	18	Survival factor	90.00%
the lumen maintenance factor	96.00%		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0.90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	/	If yes then replacement claim (W)	/
Flicker metric (Pst LM)	1.0	Stroboscopic effect metric (SVM)	0.4

Remarks:

3. Information requirements

From 1 Sepember 2021 the following information requirements shall apply:

(a) Information to be displayed on the light source itself

For all light sources, except CTLS, LFL, CFLni, other FL, and HID, the value and physical unit of the useful luminous flux (lm) and correlated colour temperature (K) shall be displayed in a legible font on the surface if, after the inclusion of safety-related information, there is sufficient space available for it without unduly obstructing the light emission.

For directional light sources, the beam angle (°) shall also be indicated.

If there is room for only two values, the useful luminous flux and the correlated colour temperature shall be displayed. If there is room for only one value, the useful luminous flux shall be displayed.

(b) Information to be visibly displayed on the packaging

(1) Light source placed on the market, not in a containing product

If a light source is placed on the market, not in a containing product, in a packaging containing information to be visibly displayed at a point-of-sale prior to its purchase, the following information shall be clearly and prominently displayed on the packaging:

(a) the useful luminous flux (Φuse) in a font at least twice as large as the display of the on-mode power (Pon), clearly indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°);

(b) the correlated colour temperature, rounded to the nearest 100 K, also expressed graphically or in words, or the range of correlated colour temperatures that can be set;

(c) the beam angle in degrees (for directional light sources), or the range of beam angles that can be set;

(d) electrical interface details, e.g. cap- or connector-type, type of power supply (e.g. 230 V AC 50 Hz, 12 V DC);

(e) the L70B50 lifetime for LED and OLED light sources, expressed in hours;

(f) the on-mode power (Pon), expressed in W;

(g) the standby power (Psb), expressed in W and rounded to the second decimal. If the value is zero, it may be omitted from the packaging;

(h) the networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal. If the value is zero, it may be omitted from the packaging;

(i) the colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set;

(j) if CRI< 80, and the light source is intended for use in outdoor applications, industrial applications or other applications where lighting standards allow a CRI< 80, a clear indication to this effect. For HID light sources with useful luminous flux > 4 000 lm, this indication is not mandatory;

(k) if the light source is designed for optimum use in non-standard conditions (such as ambient temperature Ta ≠ 25 °C or specific thermal management is necessary): information on those conditions;

(l) a warning if the light source cannot be dimmed or can be dimmed only with specific dimmers or with specific wired or wireless dimming methods. In the latter cases a list of compatible dimmers and/or methods shall be provided on the manufacturer's website;

(m) if the light source contains mercury: a warning of this, including the mercury content in mg rounded to the first decimal place;

(n) if the light source is within the scope of Directive 2012/19/EU, without prejudice to marking obligations pursuant to Article 14(4) of Directive 2012/19/EU, or contains mercury: a warning that it shall not be disposed of as unsorted municipal waste.

Items (a) to (d) shall be displayed on the packaging in the direction meant to face prospective buyer; for other items this is also recommended, if space permits.

For light sources that can be set to emit light with different characteristics, the information shall be reported for the reference control settings. In addition, a range of obtainable values may be indicated.

The information does not need to use the exact wording on the list above. Alternatively, it may be displayed in the form of graphs, drawings or symbols.


(e) Information for products specified in point 3 of Annex III

For the light sources and separate control gears specified in point 3 of Annex III the intended purpose shall be stated in the technical documentation for compliance assessment as per Article 5 of this Regulation and on all forms of packaging, product information and advertisement, together with an explicit indication that the light source or separate control gear is not intended for use in other applications.

The technical documentation file drawn up for the purposes of conformity assessment, in accordance with Article 5 of this Regulation shall list the technical parameters that make the product design specific to qualify for the exemption.

In particular for light sources indicated in point 3(p) of Annex III it shall be stated: 'This light source is only for use by photo sensitive patients. Use of this light source will lead to increased energy cost compared to an equivalent more energy efficient product.'

Product photos of EUT:

Photo 1	
Photo 2	

*** End of the report ***